


Transient Voltage Suppressor Diodes


Uni-directional



Features

- Excellent clamping capability
- Low dynamic impedance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Bi-directional



Mechanical Data

- **Package:** R-6
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes cathode end

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Max
Peak power dissipation, with a 10/1000us waveform ⁽¹⁾	P_{PPM}	W	5000
Peak pulse current, with a 10/1000us waveform ⁽¹⁾	I_{PPM}	A	See Next Table
Power dissipation, on infinite heat sink at TL=75°C	P_D	W	8.0
Peak forward surge current, 8.3 ms single half sine-wave unidirectional only ⁽²⁾	I_{FSM}	A	600
Operating junction and storage temperature range	T_J, T_{STG}	°C	-55 to +150

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Maximum instantaneous forward voltage at 25A for unidirectional only	V_{FM}	V	3.5

Notes:

- (1) Non-repetitive current pulse, per Fig. 3 and derated above $T_A = 25^\circ\text{C}$ per Fig.2.
- (2) Measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.

■Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
5KP SERIES	D1	Approximate 2.30	500	500	5000	Tape
5KP SERIES	C1	Approximate 2.30	100	100	5000	Bulk



5KP SERIES

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

Part Number (Uni)	Part Number (Bi)	Breakdown Voltage V _{BR} @I _T			Maximum Reverse Leakage I _R @ V _{WM} (μA)	Working Peak Reverse Voltage V _{RWM} (V)	Maximum Reverse Surge Current I _{PP} (A)	Maximum Clamping Voltage V _c @ I _{PP} (V)	Maximum Temperature Coefficient of V _{BR} (%/°C)
		Min (V)	Max (V)	I _T (mA)					
5KP5.0A	5KP5.0CA	6.4	7	50	2000	5	543	9.2	0.057
5KP6.0A	5KP6.0CA	6.67	7.37	50	5000	6	485	10.3	0.061
5KP6.5A	5KP6.5CA	7.22	7.98	50	2000	6.5	446	11.2	0.065
5KP7.0A	5KP7.0CA	7.78	8.6	50	1000	7	417	12	0.068
5KP7.5A	5KP7.5CA	8.33	9.21	5	250	7.5	388	12.9	0.073
5KP8.0A	5KP8.0CA	8.89	9.83	5	150	8	368	13.6	0.075
5KP8.5A	5KP8.5CA	9.44	10.4	5	50	8.5	347	14.4	0.078
5KP9.0A	5KP9.0CA	10	11.1	5	20	9	325	15.4	0.081
5KP10A	5KP10CA	11.1	12.3	5	15	10	294	17	0.084
5KP11A	5KP11CA	12.2	13.5	5	10	11	275	18.2	0.086
5KP12A	5KP12CA	13.3	14.7	5	5	12	251	19.9	0.088
5KP13A	5KP13CA	14.4	15.9	5	2	13	233	21.5	0.09
5KP14A	5KP14CA	15.6	17.2	5	2	14	216	23.2	0.092
5KP15A	5KP15CA	16.7	18.5	5	2	15	205	24.4	0.094
5KP16A	5KP16CA	17.8	19.7	5	2	16	192	26	0.096
5KP17A	5KP17CA	18.9	20.9	5	2	17	181	27.6	0.097
5KP18A	5KP18CA	20	22.1	5	2	18	171	29.2	0.098
5KP20A	5KP20CA	22.2	24.5	5	2	20	154	32.4	0.099
5KP22A	5KP22CA	24.4	26.9	5	2	22	141	35.5	0.1
5KP24A	5KP24CA	26.7	29.5	5	2	24	129	38.9	0.101
5KP26A	5KP26CA	28.9	31.9	5	2	26	119	42.1	0.101
5KP26A	5KP26CA	28.9	31.9	5	2	26	119	42.1	0.101
5KP28A	5KP28CA	31.1	34.4	5	2	28	110	45.4	0.102
5KP30A	5KP30CA	33.3	36.8	5	2	30	103	48.4	0.103
5KP33A	5KP33CA	36.7	40.6	5	2	33	93.8	53.3	0.104
5KP36A	5KP36CA	40	44.2	5	2	36	86.1	58.1	0.104
5KP40A	5KP40CA	44.4	49.1	5	2	40	77.5	64.5	0.105
5KP43A	5KP43CA	47.8	52.8	5	2	43	72	69.4	0.105
5KP45A	5KP45CA	50	55.3	5	2	45	68.8	72.7	0.106
5KP48A	5KP48CA	53.3	58.9	5	2	48	64.6	77.4	0.106
5KP51A	5KP51CA	56.7	62.7	5	2	51	60.7	82.4	0.107
5KP54A	5KP54CA	60	66.3	5	2	54	57.4	87.1	0.107
5KP58A	5KP58CA	64.4	71.2	5	2	58	53.4	94	0.107
5KP60A	5KP60CA	66.7	73.7	5	2	60	51.7	97	0.108
5KP64A	5KP64CA	71.1	78.6	5	2	64	48.5	103	0.108
5KP70A	5KP70CA	77.8	86	5	2	70	44.2	113	0.108
5KP75A	5KP75CA	83.3	92.1	5	2	75	41.3	121	0.108
5KP78A	5KP78CA	86.7	95.8	5	2	78	39.7	126	0.108
5KP85A	5KP85CA	94.4	104	5	2	85	36.5	137	0.11
5KP90A	5KP90CA	100	111	5	2	90	34.2	146	0.11
5KP100A	5KP100CA	111	123	5	2	100	30.9	162	0.11
5KP110A	5KP110CA	122	135	5	2	110	28.2	177	0.112



5KP SERIES

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Part Number (Uni)	Part Number (Bi)	Breakdown Voltage V _{BR} @I _T			Maximum Reverse Leakage I _R @ V _{WM} (μA)	Working Peak Reverse Voltage V _{RWM} (V)	Maximum Reverse Surge Current I _{PP} (A)	Maximum Clamping Voltage V _c @ I _{PP} (V)	Maximum Temperature Coefficient of V _{BR} (%/°C)
		Min (V)	Max (V)	I _T (mA)					
5KP120A	5KP120CA	133	147	5	2	120	25.9	193	0.112
5KP130A	5KP130CA	144	159	5	2	130	23.9	209	0.112
5KP150A	5KP150CA	167	185	5	2	150	20.6	243	0.112
5KP160A	5KP160CA	178	197	5	2	160	19.3	259	0.112
5KP170A	5KP170CA	189	209	5	2	170	18.2	275	0.112
5KP188A	5KP188CA	209	231	5	2	188	15.2	328	0.112

Notes:

For bi-directional types having VWM of 10V and less, the I_R limit is doubled.

■ Characteristics (Typical)

FIG1: Peak Pulse Power Rating Curve




FIG3: Pulse Waveform




FIG4: Pulse Power or Current vs Initial Junction Temperature






FIG4: Power Derating Curve






5KP SERIES



■ Outline Dimensions



R-6		
Dim	Min	Max
A	8.60	9.10
B	8.60	9.10
C	25.4	/
D	1.20	1.32



5KP SERIES

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.