



## Bridge Rectifiers



### Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

### Mechanical Data

- **Package:** 6KBJ  
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

### ■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GBJ30A	GBJ30B	GBJ30D	GBJ30G	GBJ30J	GBJ30K	GBJ30M	
Device marking code			GBJ30A	GBJ30B	GBJ30D	GBJ30G	GBJ30J	GBJ30K	GBJ30M	
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000	
Maximum RMS Voltage	VRMS	V	35	70	140	280	420	560	700	
Maximum DC blocking Voltage	VDC	V	50	100	200	400	600	800	1000	
Average rectified output current @60Hz sine wave, R-load	IO	A	With heatsink Tc =100°C							30.0
			Without heatsink Ta =25°C							4.0
Forward Surge Current (Non-repetitive) @8.3ms, Half-sine wave, 1 cycle, Tj=25°C	IFSM	A								350
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C										700
Current squared time @1ms≤t≤8.3ms Tj=25°C, Rating of per diode	I <sup>2</sup> t	A <sup>2</sup> s								508
Storage temperature	Tstg	°C								-55 ~ +150
Junction temperature	Tj	°C								-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute	Vdis	KV								2.5
Mounting torque @Recommend torque: 5kg·cm	Tor	kg·cm								8

### ■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GBJ30A	GBJ30B	GBJ30D	GBJ30G	GBJ30J	GBJ30K	GBJ30M	
Maximum instantaneous forward voltage drop per diode	VF	V	IFM=15.0A								1.0
Maximum DC reverse current at rated DC blocking voltage per diode	IR	μA	Tj=25°C								5
			Tj=125°C								100
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C								108



# GBJ30A THRU GBJ30M

## ■ Thermal Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	GBJ30A	GBJ30B	GBJ30D	GBJ30G	GBJ30J	GBJ30K	GBJ30M
Thermal Resistance	Between junction and ambient, Without heatsink	R <sub>θJ-A</sub>	°C/W	18.0						
	Between junction and case, With heatsink	R <sub>θJ-C</sub>		0.8						

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

## ■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBJ30ATHRU GBJ30M	B1	Approximate 6.5	15	750	1500	TUBE

## ■ Characteristics (Typical)

FIG1: I<sub>o</sub>-T<sub>c</sub> Curve




FIG2: Surge Forward Current Capability




FIG3: Typical Forward Voltage






FIG4: Typical Reverse Characteristics





# GBJ30A THRU GBJ30M

## ■ Outline Dimensions



6KBJ-L		
Dim	Min	Max
A	29.7	30.3
B	19.7	20.3
C	17.0	18.0
D	5.3	6.3
E	3.8	4.2
F	7.3	7.7
G	9.8	10.2
H	0.9	1.1
I	2.0	2.4
J	2.3	2.7
K	3.4	3.8
L	4.4	4.8
M	10.8	11.2
N	3.1	3.7
O	3.1	3.4
P	0.35	0.65



## GBJ30A THRU GBJ30M

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.